

PRODUCT CARD


Short name


AKCW-KD3-(5000)

Full name

Self adhesive tile edge rubber block for perimeter - thickness 3,5 mm


BASE DATA

Product group	Accessories
Application	• terrace tiles • raised deck terraces • terrace pedestals • terrace joist
Code	110.068011
EAN	5 9 0 4 2 7 6 3 4 4 1 4 9  5 9 0 4 2 7 6 3 4 4 1 4 9



TECHNICAL DATA

Minimum height	3 mm
Maximum height	3 mm
Total dimension - length	25 mm
Total dimension - width	15 mm
Total product dimensions - height	3 mm
Head diameter (top plate) Ø 0 mm (0 cm2)	
Base diameter	Ø 0 mm (0 cm2)
Weight	~0 kg



Wytrzymałość na obciążenia do	0 kg
Fire resistance	E
Temperature range	od -10°C do 65°C
Color	black
Mandatory warranty	Limited 10-year residential and commercial warranty
Country of origin	Poland
Material name	EPDM- roll thickness 3 mm
Percentage of recycled material	0 %
Type of waste	• non-hazardous waste - recyclable
Project type	• exterior use

What finishing materials can be used




- concrete paver
- stone pavers
- ceramic tile
- hardwood joist
- softwood joist
- aluminium joist
- WPC joist

Consists of

Self-adhesive expansion wedge 3 mm

CERTIFICATES

Product certified by the Building Research Institute.
NATIONAL TECHNICAL ASSESSMENT ITB-KOT-2022-2174



LOGISTICS INFORMATION

Package	Quantity Packaging Value	Package weight	Empty package weight	Palett	Number of packages on a pallet	Number of pieces on a pallet	Pallet weight	Empty pallet weight
BOX 300x250x200	5000	10 kg	0.24 kg	WOODEN PALLET 120x100x220	160	800000	1656 kg	18 kg

Characteristic features

Features of the accessory:

1. Creates a 3 mm gap between the paver and the terrace edge restraint
2. Protects building elements from moisture
3. Prevents paver displacement
4. Adhered to the side edge of pavers

Application

Application of raised deck terraces:

The raised deck terrace system finds wide application in modern residential, commercial, and public utility construction. This solution is intended for creating:

1. terraces, balconies, and loggias
2. usable roofs and green roofs
3. recreational areas around buildings
4. pedestrian walkways, decks, and squares
5. spaces above technical installations requiring easy service access.

The system enables quick installation without the use of mortars and adhesives, ensuring free water drainage and ventilation under the entire terrace surface. Thanks to adjustable pedestals and/or joist construction, it allows for leveling slopes and height differences in the substrate.

Raised deck terraces are a particularly recommended solution where the following are important:

1. durability and resistance to weather conditions
2. aesthetic appearance and even surface
3. easy access to the insulation layer and installations
4. possibility of quick modernization or surface replacement

Creates gaps between the paver and the terrace edge restraint.

Advantages

Advantages of raised deck terraces:

1. Height and level adjustment – possibility of precise leveling of the surface without the need for screeds
2. Effective drainage – gaps in the terrace drain water to the space under the terrace
3. Easy maintenance – access to installations and substrate without dismantling the entire structure
4. Easy maintenance – access to installations and substrate without dismantling the entire structure
5. Thermal and acoustic insulation – the air layer under the pavers improves user comfort
6. Quick installation and dismantling – possibility of reusing elements when changing the arrangement
7. Durability – resistance to weather conditions and usage loads

Advantages of the accessory:

1. The self-adhesive rubber shim allows for the creation of an expansion joint between the last terrace paver and the wall

Installation recommendations

A raised deck terrace does not require permanent anchoring to the substrate. Free water drainage and ventilation must be ensured under the entire surface of the terrace. The substrate must be level, stable, and load-bearing. A slope of at least 1.5–2% towards the drainage must be provided. In the case of higher loads, densify the support grid. Level the terrace height by adjusting the pedestals. At building expansion joints, maintain a gap and seal

it with flexible elements. Pedestals cannot be stacked on top of each other - meaning the base of the upper pedestal cannot be placed on the top cap of the lower pedestal. The holes in the base are only for stacking pedestals during packaging.

Clean the edge of the terrace paver from dust. Degrease with petroleum ether. After evaporation, stick the self-adhesive wedge. If the pedestal is set on too soft a substrate, the deflection of the paver when walking may cause the wedges to protrude above the edge of the paver.

Tools

- Measure - Spirit level - String line or cross line laser - Pencil or construction marker - Mason's rule - Rubber mallet - Work gloves - Safety glasses - Hearing protection - Dust mask - Metal saw blade or jigsaw with metal cutting blade for trimming elements

Extraction gasoline. Protective gloves.

Recommendations for use

The raised deck terrace is intended for use in accordance with its purpose – as a recreational surface. Do not point-load the pavers (e.g., by placing very heavy objects on a small area). Avoid mechanical impacts that could damage the pavers or the support structure. The terrace surface should be regularly swept, and leaves, sand, and debris that may accumulate in the joints should be removed. At least once a year, check the stability of the pavers and pedestals. After winter or heavy rainfall, check the drainage system for blockages. If looseness or damage is found – perform adjustment or replacement of the elements. If access to the space under the pavers is required (e.g., for installations, drains), they should be carefully lifted using appropriate lifters or lifting tools. If access to the space under the pavers is required (e.g., for installations, drains), they should be carefully lifted using appropriate lifters or lifting tools. In the case of a slippery surface, use anti-slip mats or additional protective coatings, e.g., around the pool.