

PRODUCT CARD

Short name

DEC-T5X30ZN-(2000)


Full name

Hidden deck fastener DECK-DRY screw for joists (wood, WPC, aluminium) 5X30 - galvanized black

BASE DATA

Product group	Deck-Dry
Application	• wooden decking • wpc decking boards
Code	301.020111

EAN



TECHNICAL DATA

Minimum height	0 mm
Maximum height	0 mm
Total dimension - length	6 mm
Total dimension - width	6 mm
Total product dimensions - height	30 mm
Head diameter (top plate)	Ø 0 mm (0 cm2)
Base diameter	Ø 0 mm (0 cm2)
Weight	~0 kg
Wytrzymałość na obciążenia do	0 kg
Fire resistance	E

Temperature range	od -20°C do 65°C
Color	silver
Mandatory warranty	Limited 10-year residential and commercial warranty
Country of origin	Poland
Material name	Galvanized steel
Percentage of recycled material	0 %
Type of waste	• non-hazardous waste - recyclable
Project type	• exterior use
What finishing materials can be used • wooden decking boards	

Consists of
Screw 5x30 Zinc

CERTIFICATES

Product certified by the Building Research Institute. NATIONAL TECHNICAL ASSESSMENT ITB-KOT-2022-2174



LOGISTICS INFORMATION

Package	Quantity Packaging Value	Package weight	Empty package weight	Palett	Number of packages on a pallet	Number of pieces on a pallet	Pallet weight	Empty pallet weight
BOX 300x250x200	2000	4 kg	0.24 kg	WOODEN PALLET 120x100x220	160	320000	696 kg	18 kg

Characteristic features

Patented terrace installation system that increases the durability of decking boards

Features of the accessory:

1. Dedicated screw for mounting DECK-DRY connectors in the gap between deck boards
2. Made of galvanized steel
3. Can be mounted in aluminum joists after pre-drilling

Application

Designed for raised deck terraces with wooden boards, where an elevated level of durability and resistance to rot is required.

Invisible board mounting from underneath - boards are not damaged by screws from the top.

Used for mounting DECK-DRY connectors with decking boards to joists and mounting WPC clips with boards to joists.

Advantages

Advantages of the accessory:

1. Durability
2. Versatility of application

Installation recommendations

Screws should be screwed in with the clutch on the cordless screwdriver set appropriately. For the installation of DECK-DRY connectors, use the dedicated T20 DEC-BIT20 bit. Installing screws into aluminum joists may require pre-drilling the joists.

Tools

Torx bit Drill bit 3.5 mm

Recommendations for use

Do not use de-icing salt. Salt can cause corrosion of metal structural elements (screws, clips, adjustable feet) and damage surfaces adjacent to the terrace.