

PRODUCT CARD


Short name

DECS-RP-(1)

Full name



LockDown rubber shim – 115x115 mm, thickness 1 mm

BASE DATA

Product group	DeckSafe
Code	108.090111
EAN	5 9 0 4 2 7 6 3 4 6 0 5 1  5 9 0 4 2 7 6 3 4 6 0 5 1

TECHNICAL DATA

Minimum height	0 mm
Maximum height	0 mm
Total dimension - length	115 mm
Total dimension - width	115 mm
Total product dimensions - height	1 mm
Weight	~0.02 kg
Wytrzymałość na obciążenia do	0 kg
Temperature range	od -20°C do
Color	black
Mandatory warranty	Limited 10-year residential and commercial warranty
Country of origin	Poland




Material name	Thermoplastic elastomer - black regranulate
Percentage of recycled material	100 %

Consists of
Rubber shim LockDown

CERTIFICATES

Product certified by the Building Research Institute.
NATIONAL TECHNICAL ASSESSMENT ITB-KOT-2022-2174



LOGISTICS INFORMATION

Package	Quantity Packaging Value	Package weight	Empty package weight	Palett	Number of packages on a pallet	Number of pieces on a pallet	Pallet weight	Empty pallet weight
-	-	- kg	- kg	-	-	-	- kg	- kg

Characteristic features

Characteristics of DeckSafe

- Enhancing the application possibilities and safety of raised deck terraces

Characteristics of the accessory:

- Rubber shim for the LockDown Sunny Brook system

Application

Application of raised deck terraces:

The raised deck terrace system finds wide application in modern residential, commercial, and public utility construction. This solution is intended for creating:

- terraces, balconies, and loggias
- usable roofs and green roofs
- recreational areas around buildings
- pedestrian walkways, decks, and squares

5. spaces above technical installations requiring easy service access.

The system enables quick installation without the use of mortars and adhesives, ensuring free water drainage and ventilation under the entire terrace surface. Thanks to adjustable pedestals and/or joist construction, it allows for leveling slopes and height differences in the substrate.

Raised deck terraces are a particularly recommended solution where the following are important:

1. durability and resistance to weather conditions
2. aesthetic appearance and even surface
3. easy access to the insulation layer and installations
4. possibility of quick modernization or surface replacement

Projects requiring specialized solutions in the field of safety and functionality.

Used between the LockDown protective tile and the concrete paver for sound dampening and additional pressure.

Advantages

Advantages of raised deck terraces:

1. Height and level adjustment – possibility of precise leveling of the surface without the need for screeds
2. Effective drainage – gaps in the terrace drain water to the space under the terrace
3. Easy maintenance – access to installations and substrate without dismantling the entire structure
4. Easy maintenance – access to installations and substrate without dismantling the entire structure
5. Thermal and acoustic insulation – the air layer under the pavers improves user comfort
6. Quick installation and dismantling – possibility of reusing elements when changing the arrangement
7. Durability – resistance to weather conditions and usage loads

Advantages of the accessory:

1. Dampens sound and improves the hold of the LockDown protective tile.

Installation recommendations

A raised deck terrace does not require permanent anchoring to the substrate. Free water drainage and ventilation must be ensured under the entire surface of the terrace. The substrate must be level, stable, and load-bearing. A slope of at least 1.5–2% towards the drainage must be provided. In the case of higher loads, densify the support grid. Level the terrace height by adjusting the pedestals. At building expansion joints, maintain a gap and seal it with flexible elements. Pedestals cannot be stacked on top of each other - meaning the base of the upper pedestal cannot be placed on the top cap of the lower pedestal. The holes in the base are only for stacking pedestals during packaging.

Place between the LockDown protective tile and the concrete paver.

Tools

- Measure - Spirit level - String line or cross line laser - Pencil or construction marker - Mason's rule - Rubber mallet - Work gloves - Safety glasses - Hearing protection - Dust mask - Metal saw blade or jigsaw with metal cutting blade for trimming elements

Manual installation: Installation does not require the use of specialized tools.

Recommendations for use

The raised deck terrace is intended for use in accordance with its purpose – as a recreational surface. Do not point-load the pavers (e.g., by placing very heavy objects on a small area). Avoid mechanical impacts that could damage the pavers or the support structure. The terrace surface should be regularly swept, and leaves, sand, and debris that may accumulate in the joints should be removed. At least once a year, check the stability of the pavers and pedestals. After winter or heavy rainfall, check the drainage system for blockages. If looseness or damage is found – perform adjustment or replacement of the elements. If access to the space under the pavers is required (e.g., for installations, drains), they should be carefully lifted using appropriate lifters or lifting tools. If access to the space under the pavers is required (e.g., for installations, drains), they should be carefully lifted using appropriate lifters or lifting tools. In the case of a slippery surface, use anti-slip mats or additional protective coatings, e.g., around the pool.